

# ACCESSORIES PLAN

Standard Accessories - Optional Accessories

---



**ATTENTION**



**On order specify: type of machine, serial number, item code and quantity.**

**A la commande: bien préciser le type de la machine, le n° de serie, la reference de pièce, la quantité.**

**Bei Auftragserteilung anzugeben: Maschinentype, Seriennummer, Artikel-Code, Menge.**

**All'ordine specificare: tipo macchina e matricola, codice e quantità del particolare.**








**En cada pedido hay que especificar: el tipo de máquina y su número de matrícula, el número de código de la pieza requerida y su cantidad.**

**Na encomenda especificar: tipo da máquina e número de série, código do item e quantidade.**



**Notice:** The information contained in this document is subject to change without notice

---

**STANDARD - Accessories**

	<b>EAA0377G23A</b>  <b>EAA0377G23A</b>	SMART BEAD SPACER	Holds the bead in 6 positions in the drop center during tire mounting operation. To be used in conjunction with the pneumatic bead assist.
	<b>EAA0408G33A</b>  <b>EAA0408G33A</b>	PLASTIC TYRE PROTECTOR	Clip-on type, to protect run-flat tyres when mounted onto steel rims, 1 off It replaces the previous P/N EAA0332G38A.
	<b>4026853</b>  <b>EAA0304G52A</b>	PLASTIC RIM PROTECTIONS	Clip-on type, to protect rim from scratches, set of 3.
	<b>4030319</b>  <b>EAA0350G07A</b>	PLASTIC PROTECTORS	5 Sets of plastic rim protectors for car & m/c mounting heads 4029196, consisting of 5 plastic rim protectors, 5 rear protectors, 2 M5 hex nuts
	<b>EAC0115G06A</b>  <b>EAC0115G06A</b>	PLASTIC PROTEC. FOR BEAD LEVER WAVE PLUS	Plastic protector for bead lever wave plus 34415
	<b>4029196</b>  <b>EAA0329G95A</b>	MOUNTING HEAD	With support, for retrofit on all tire changers manufactured by snap-on in correggio protections kit 4030319
	<b>1419</b>  <b>EAA0304G16A</b>	BRUSH	For tire lubrication



<b>STANDARD - Accessories</b>			
	<p><b>34415</b></p> <p><b>EAC0097G47A</b></p>	<p>BEAD LEVER WAVE PLUS</p>	<p>Wave tyre lever certified by WDK, comes standard with all tyre changers Alternative for former short tyre lever 1418, ALU tyre lever 30660 and WAVE ty</p>
	<p><b>4025460</b></p> <p><b>EAA0349G76A</b></p>	<p>5 KG LUBE BUCKET HOLDER</p>	<p>Ring to accommodate 5 kg lube bucket</p>









**OPTIONAL - Accessories**

	<b>EAK0317G64A</b>  <b>EAK0317G64A</b>	WHEEL LIFT	Pneumatic wheel lift, pedal-operated Capacity 70 kg Platform height 30 mm with roller board Comes standard with mont
	<b>4031295</b>  <b>EAA0358G85A</b>	WDK BEAD CLAMP	To facilitate mounting of the upper bead, especially on low profile and stiff tires.
	<b>H1977254</b>  <b>EAA0393G81A</b>	TYRE BOOSTER	With lockable release valve, 19 l air tank, pressure-relief valve, inflation up to 10 bar maximum, for car and light- truck tubeless wheels.
	<b>EAC0125G10A</b>  <b>EAC0125G10A</b>	TYRE BEAD HOLDER	Universal tool to hold the bead in the rim's drop center while mounting the tyre
	<b>EAA0410G89A</b>  <b>EAA0410G89A</b>	THREADED SHAFT ASSY	For 4030515 (closed centre rims kit) when it is used on quickLOK™ clamping system
	<b>EAA0376G54A</b>  <b>EAA0376G54A</b>	STEEL ROLLER AND PINS FOR MOUNTING HEAD	Steel roller with pin for mounting head EAA0329G95A and EAA0304G35A. For mounting heads 4029196
	<b>EAM0146G66</b>  <b>EAM0146G66</b>	SPECIAL RUBBER CONE	For manual or quickLOK™ centre post TC (polyamide), ideal for alloy rims e.g. of Porsche and Audi.

**OPTIONAL - Accessories**

	<b>EAA0377G15A</b>  <b>EAA0377G15A</b>	SPACER KIT	For all centre post tyre changers. To lock special rims with a projecting profile centring ring. The spacer guarantees a secure conta
	<b>EAA0440G53A</b>  <b>EAA0440G53A</b>	SPACER FOR BEAD BREAKER 70mm	Stop the bead breaker blade at a convenient distance from the pad avoiding damage to run-flat tyres - spare part -
	<b>EAA0440G52A</b>  <b>EAA0440G52A</b>	SPACER FOR BEAD BREAKER 50mm	Stop the bead breaker blade at a convenient distance from the pad avoiding damage to run-flat tyres - spare part -
	<b>EAA0440G51A</b>  <b>EAA0440G51A</b>	SPACER FOR BEAD BREAKER 20mm	Stop the bead breaker blade at a convenient distance from the pad avoiding damage to run-flat tyres - spare part -
	<b>EAA0393G04A</b>  <b>EAA0393G04A</b>	SMART BEAD SPACER - LOW PROFILE	Holds the bead in 6 positions in the drop center during tire mounting operation. To be used in conjunction with the pneumatic bead assist - B
	<b>EAA0363G30A</b>  <b>EAA0363G30A</b>	SET OF SPHERICAL HEAD BOLTS	Head dia. 28 mm Special bolt for Audi Q5 + Q7 Set of 5 For closed-centre rim kits EAA0410G88A + 4030515
	<b>EAA0363G40A</b>  <b>EAA0363G40A</b>	SET OF SPHERICAL HEAD BOLTS	Head dia. 28 mm Special bolt for Audi A7 + A8 Set of 5 For closed-centre rim kits EAA0410G88A + 4030515
	<b>EAA0384G83A</b>  <b>EAA0384G83A</b>	SET OF BOLTS - LAND ROVER DEFENDER	Tapered vertex diameter = 36 mm Overall length = 100 mm Set of 5 bolts w/ tapered vertex For reverse-mounted whee

**OPTIONAL - Accessories**

	<b>EAA0364G48A</b>  <b>EAA0364G48A</b>	SET OF BOLTS	Length = 110 mm Set of 5 bolts w/ cylindrical vertex Set of 5 bolts w/ tapered vertex For reverse-mounted wheel
	<b>EAA0440G50A</b>  <b>EAA0440G50A</b>	SET OF BOLTS	Cylindrical vertex diameter = 19 mm Overall length = 110 mm Set of 5 bolts w/ cylindrical vertex For reverse-mounted wheel
	<b>4031245</b>  <b>EAA0358G58A</b>	REVERSE- MOUNTED WHEEL KIT	To clamp reverse mounted wheels on center post clamping system 5 cylindrical vertex pins of 24 mm diameter 5 conical vertex pins of 24
	<b>4028228</b>  <b>EAA0304G66A</b>	QUICK EXCHANGE DEVICE	With plastic mounting head
	<b>4028229</b>  <b>EAA0304G67A</b>	QUICK EXCHANGE DEVICE	Including plastic mounting head for VW / Audi / Ford / Peugeot rims with protruding spokes
	<b>4029892</b>  <b>EAA0344G94A</b>	QUICK EXCHANGE DEVICE	Without mounting head to be used with all types of Snap-on car TC mounting heads. Standard on VAS 6313 C, 6314 C, 6346 C
	<b>EAA0481G31A</b>  <b>EAA0481G31A</b>	PLASTIC TYRE PROTECTOR, CLIP-ON TYPE	To protect run-flat tyres when mounted onto steel rims Set of 3
	<b>EAK0317G33A</b>  <b>EAK0317G33A</b>	PLASTIC PROTECTORS 85 mm	Cone dia. 85 mm and EAK0317G32A cone kit 42- 85 mm The kit contains 10 protectors

**OPTIONAL - Accessories**

	<b>EAA0356G20A</b>  <b>EAA0356G20A</b>	PLASTIC PROTECTORS	Sets of plastic rim protectors for mounting head EAA0332G36A - rims with protruding spokes
	<b>EAC0115G26A</b>  <b>EAC0115G26A</b>	PLASTIC PROTECTOR FOR WHEEL LIFT ARM	To be clipped onto lift EAK0317G64A arm in order to protect rims from being scratched For centre post tyre changer with standard tool
	<b>4024784</b>  <b>EAA0247G20A</b>	PLASTIC MOUNTING HEAD	With support, for retrofit on all tire changers manufactured by Snap-on - Correggio.
	<b>4027646</b>  <b>EAA0304G37A</b>	PLASTIC MOUNTING HEAD	With support, for VW / Audi / Ford / Peugeot rims with protruding spokes
	<b>EAA0393G89A</b>  <b>EAA0393G89A</b>	MOUNTING TOOL	Stand-alone mounting tool to facilitate the operation with run-flat tyres For use on quadriga TC. On semi-automatic centre-post TC only in conjunction
	<b>4028884</b>  <b>EAA0329G27A</b>	MOUNTING HEAD ADAPTER FOR QUICK EXCHANGE	To be used when the customer already owns a quick exchange device and wants to use an additional mounting head.
	<b>4029338</b>  <b>EAA0332G36A</b>	MOUNTING HEAD	With support, for vw / audi / ford / peugeot rims with protruding spokes
	<b>EAA0393G08A</b>  <b>EAA0393G08A</b>	MH TRACTOR KIT	Tractor kit for bead depressor of PBD330, easymont pro and MH 320 pro

**OPTIONAL - Accessories**



	<b>EAK0330G20A</b>  <b>EAK0330G20A</b>	MB CLAMPING KIT	Consisting of: - 1 x EAM0091G90A Fixed flange for MB studs -112/120MM - 1 x EAM0091G91A Reduction cone to be used
	<b>EAK0317G96A</b>  <b>EAK0317G96A</b>	MAGNETIC TOOL SUPPORT	Flexible solution to position the small tools in the most comfortable place possible Maximum weight allowed: 2kg.
	<b>4030486</b>  <b>EAA0349G06A</b>	LIGHT-TRUCK WHEEL KIT	To clamp pick-up & light- truck wheels on center post clamping system. Single side cone 135-175 mm.
	<b>EAK0317G95A</b>  <b>EAK0317G95A</b>	HOLDER FOR TYRE LUBRICANT BUCKET (MAGN.)	Flexible solution to position the bucket in the most comfortable place possible
	<b>EAA0426G34A</b>  <b>EAA0426G34A</b>	CONNECTOR FOR MOUNTING TOOL	Connector to make EAA0393G89A mounting tool compatible with clamping shafts of semi- automatic centre-post TC.
	<b>EAK0317G76A</b>  <b>EAK0317G76A</b>	CONE KIT 75 mm	For manual or quickLOK™ centre post tyre changers Centring cones, 75 mm diameter, for wheel clamping, consisting of 5 plastic cones
	<b>EAK0317G75A</b>  <b>EAK0317G75A</b>	CONE KIT 64 mm	For manual or quickLOK™ centre post tyre changers Centring cones, 64 mm diameter, for wheel clamping, consisting of 5 plastic cones
	<b>EAK0317G32A</b>  <b>EAK0317G32A</b>	CONE KIT 42-85 mm	For manual or quickLOK™ centre post TC consisting of 1 steel cone EAM0117G47A to centre steel / alloy wheels before clamping and 3 plastic prot





<b>OPTIONAL - Accessories</b>			
	<p><b>EAK0317G78A</b> <b>EAK0317G78A</b></p>	<p>CONE KIT 145 mm</p>	<p>For manual or quickLOK™ centre post tyre changers Centring cones, 145 mm diameter, for wheel clamping, consisting of 5 plastic cones</p>
	<p><b>EAK0317G77A</b> <b>EAK0317G77A</b></p>	<p>CONE KIT 126 mm</p>	<p>For manual or quickLOK™ centre post tyre changers Centring cones, 126 mm diameter, for wheel clamping, consisting of 5 plastic cones</p>
	<p><b>EAA0410G88A</b> <b>EAA0410G88A</b></p>	<p>CLOSED- CENTRE RIM KIT</p>	<p>To clamp closed centre rims on quickLOK™ clamping system (compact clamping device included)</p>
	<p><b>EAA0392G80A</b> <b>EAA0392G80A</b></p>	<p>BMW CLAMPING KIT</p>	<p>For standard and reverse mounted wheels, consisting of: Cylindrical vertex pin L.110mm. Tapered vertex pin L.110m</p>
	<p><b>4003444</b> <b>EAA0247G70A</b></p>	<p>BEAD DEPRESSING TOOL MX</p>	<p>To facilitate mounting of the upper bead, especially on low profile and stiff tires</p>
	<p><b>4025966</b> <b>EAA0304G48A</b></p>	<p>BEAD DEPRESSING ROLLER</p>	<p>For quick installation on mounting head Suitable for all machines manufactured after June 2002 (sr. no. starting 0702)</p>
	<p><b>26582</b> <b>EAA0304G15A</b></p>	<p>BEAD BREAKER BLADE PROTECTOR</p>	<p>Plastic protection for bead breaker blade.</p>
	<p><b>19180</b> <b>EAK0257G98A</b></p>	<p>5 KG LUBRICANT FOR TIRES</p>	<p>5 kg lubricant for tires</p>



<b>OPTIONAL - Accessories</b>			
	<p><b>20651</b> <b>EAK0257G42A</b></p>	<p>1 KG LUBRICANT FOR TIRES</p>	<p>1 kg lubricant for tires</p>
	<p><b>4028629</b> <b>EAA0304G80A</b></p>	<p>+4 QUICK EXCHANGE DEVICE</p>	<p>To be used in conjunction with the +4 sliding jaws</p>



