


928B
Zwölfkant-Steckschlüssel


UNI/ISO 2725

	art.	\varnothing mm	\varnothing mm	L mm	$\varnothing 1$ mm	A mm	\bar{m} g
009280119	928B 19	19	29,2	50	34	14,0	171
009280121	928B 21	21	30,0	51	34	14,0	
009280122	928B 22	22	31,3	53	34	14,0	201,3
009280123	928B 23	23	33,3	53	34	14,0	214,6
009280124	928B 24	24	34,5	53	34	16,0	210
009280126	928B 26	26	36,8	55	35	16,0	255
009280127	928B 27	27	38,0	56	35	18,0	234
009280128	928B 28	28	39,0	57	35	18,0	240
009280129	928B 29	29	40,2	58	35	20,0	243
009280130	928B 30	30	41,5	58	37	20,0	271
009280132	928B 32	32	44,3	60	37	22,0	324,6
009280133	928B 33	33	45,8	60	37	24,0	332,6
009280134	928B 34	34	46,8	60	37	24,0	359
009280135	928B 35	35	48,1	62	38	25,0	367,3
009280136	928B 36	36	49,5	64	38	26,0	474
009280138	928B 38	38	52,0	68	40	27,0	550
009280141	928B 41	41	56,0	71	40	29,0	572
009280146	928B 46	46	62,3	75	43	32,0	728
009280150	928B 50	50	67,4	80	43	35,0	975
009280155	928B 55	55	73,7	84	48	38,0	1129
009280160	928B 60	60	80,0	87	48	41,0	1288

