


TECHNICAL DATASHEET


Printed: 08/04/2013
Product Management


Transportation Europe

 Central Article Code:
 L03046G45-A
 Created:
 08/09/2005

 ETN Code or Other:
 ES 650
 Modified:
 5/26/2011







Final Outlook L0345-A Approval date 01/10/2005

PERFORMANCES

C20 (Ah): 56.0 20 h

12 V

Rc (min): 0

Voltage (V):

 Cranking (A):
 460
 EN

 Vibration:
 V3 (35Hz/6g/20h)

 Endurance:
 250 cycles@100%

Charge: CHARGED Technology: GEL

Grid: Ca/Ca

CONTAINER

COVER

Type: L03 BLACK Hold Down: B13

H.D. Adapter: No

Type: DIN BLACK

Polarity: ETN 0

Terminals: EN taper post

Terminal Adapter: No SOCI: No

Ventilation: Independent

Filter: No Lateral Plug: No

WEIGHT AND STD. DIMENSIONS

 Battery Weight (kg):
 20.80

 Volume acid (l):
 0.00

 Length (mm):
 278

 Width (mm):
 175

 Height (mm):
 190

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

PLUGS

Type: 6 x Valve+Cover GREY MEDIUM

HANDLES

Type: 2 x Integrated BLACK

OTHERS

Degassing Tube: No

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.