61000 MoS2 grease EP-2

Version du document: 2 févr. 2025

Description

Cette graisse MoS2 EP a été spécialement développée pour utilisation sous les charges les plus lourdes. Cette graisse convient particulièrement pour les applications présentant des charges élevées et des régimes bas. L'addition du disulfure de molybdène assure une très bonne lubrification, même après écoulement de la graisse en raison d'une augmentation excessive de température.

Selon les spécifications de

DIN 51502
ISO 673 / L-XCC IB2
KP2K-30

Unités d'emballage

ART. N°	VOLUME	ARTICLES PAR UNITÉ	ARTICLES PAR PALETTE
61000	0.4 kg	12	-
61500	0.5 kg	6	-
61001	1 kg	6	-
61005	5 kg	1	-
61018	18 kg	1	-

Analyses standard

TEST	VALEUR		METHOD
Colour	Black		
NLGI Classification	2		
Base Oil	Mineral		
Additive	MoS2 >3%		
Kinematic Viscosity à 40 °Celsius	100	mm2/s	
Temperature Range	-20/120	°C	
Soap Thickener	Lithium		

These characteristics are typical of current production. Variations in these characteristics may occur.

MPM International Oil Company B.V. Cyclotronweg 1 2629 HN Delft
Numéro de fax: +31 (0) 15/ 251.40.31 info@mpmoil.nl www.mpmoil.nl